



**FAST  
ACCURATE  
RELIABLE**

## KEY FEATURES

- Flexible compact modular design
- Separate sensor, processing and signal conditioning electronics
- Easy to use digital communication
- Dual wavelength technology, long term stability
- PC based software for graphing and data logging
- Simultaneous analogue current and voltage outputs

## A NEW GENERATION OF GAS SENSORS

The IRgaskiT® range of dual-beam infrared sensors, offer users high performance, true dual-beam detection infrared, temperature compensated measurement of CO<sub>2</sub>. The result is a low drift, high accuracy OEM sensor with single button calibration and optional simultaneous voltage and current outputs.

Each module of the IRgaskiT® has been designed to allow the user maximum flexibility when choosing a solution that meets their application requirements.

Digital communications are easy to utilize and IRgaskiT® PC data logging software is also available. The infrared gas sensor offers these features with the further advantages of a very compact design and low cost.

The IRgaskiT® design is ideal for a wide variety of applications particularly where space and low power consumption are important issues.

Infrared gas sensors: IRgaskiT Range

# IRGASKIT

For CO<sub>2</sub>

## TECHNICAL SPECIFICATIONS GAS MEASUREMENT RANGE

MODEL	CO <sub>2</sub>
IRgaskiT	0-10%
	0-20%
	0-30%
	0-50%
	0-100%
<b>Accuracy</b>	± 5% of range*
<b>Zero Stability</b>	± 5% of range (over 12 months)
<b>Repeatability @ Zero</b>	±1% of range
<b>Repeatability @ Span</b>	±3% of range
<b>Response Time</b>	T90 = 300 seconds
<b>Operating Temp</b>	0 - 50 °C (Sensors can withstand 90 °C in standby mode)
<b>Operating Pressure</b>	1013mbar (calibration) requires pressure correction at other pressures
<b>Power Requirements</b>	5V DC/ 7 - 13VDC depending on configuration
<b>Power Consumption</b>	0.9W
<b>Output Signal</b>	0 - 2V (linear); (Optional simultaneous 4 - 20mA and digital (RS232) outputs)
<b>Humidity</b>	Measurements are unaffected by 0 - 95% relative and humidity, non condensing
<b>Weight</b>	125g
<b>Controls</b>	Zero and Span recalibration buttons (optional)

\*Not including calibration gas tolerance

## PRODUCT APPLICATIONS

- Personal Safety
- Research
- Incubators
- An many more...



**Edinburgh  
Sensors**

4 Bain Square,  
Kirkton Campus,  
Livingston, EH54 7DQ  
United Kingdom

Tel +44 (0)1506 425 300  
Fax +44 (0)1506 425 320  
sales@edinst.com

[edinburghsensors.com](http://edinburghsensors.com)